

KAWASAKI
KX450F 2006-2008

Motocross · 449cc 4T

Safety recalls: see motoxsports.com/bikes/recalls/

Verified

14 of 15 figures read off a manual page

GEARING

Stock front sprocket	13T	🔍 p. 1-9
Stock rear sprocket	50T	🔍 p. 1-9
Chain pitch	520	🔍 p. 2-34
Stock chain links	– Not yet verified	
Stock final drive ratio	3.85 : 1	⊖ calc.

WHEELS AND TIRES

Front rim	21 x 1.60	🔍 p. 1-9
Rear rim	19 x 2.15	🔍 p. 1-9
Front tire	90/100-21 57M	🔍 p. 1-9
Rear tire	120/80-19 63M	🔍 p. 1-9

SUSPENSION

Fork	– Not yet verified	
Fork travel	315 mm (12.4 in.)	🔍 p. 1-9
Shock travel	315 mm (12.4 in.)	🔍 p. 1-9
Stock fork spring rate	– Not yet verified	
Stock shock spring rate	– Not yet verified	
Static sag, bike only	– Not yet verified	
Race sag, rider on	– Not yet verified	

SHOP NOTES

Date / hours

Sag, race / static

Tire pressure, F / R

Notes

FLUIDS AND CAPACITIES

Engine oil spec	– Not yet verified	
Engine oil capacity	1.2 L (1.3 US qt)	🔍 p. 1-8
Coolant capacity	– Not yet verified	
Fuel capacity	7.2 L (1.9 US gal)	🔍 p. 1-8

MAINTENANCE

Tire pressure (off-road)	– Not yet verified	
Chain slack	– Not yet verified	
Spark plug and gap	NGK CPR8EB-9	🔍 p. 1-8

DIMENSIONS

Seat height	965 mm (38.0 in.)	🔍 p. 1-8
Wheelbase	1 485 mm (58.46 in.)	🔍 p. 1-8
Weight	– Not yet verified	

SERVICE SPECS

Fork oil, brake fluid, coolant type, fuel octane, idle speed, valve clearance	– Not yet verified	
---	--------------------	--

Sprockets run

Clickers, fork / shock

Map or jetting

🔍 printed on the manual page shown

🔍 maker web page or spec sheet ⊖ calculated, not printed

≈ converted by MotoXSports – not yet verified

Check your own manual before ordering parts or setting up the bike.
Torque values are not published here: use the manual.